## FOOTWEAR STANDARDS AND FEATURES





	The	Jan.														2
	XTLZST	XTLZWHE	XTLZBK	ХТΖВК	TORBK	DUNEBR	DUNEBK	WOLFBK	DUTYBK	GRIZZLYBK	RIDGECT	TRADEBK	NEOBKO	INCAGSBKGY	MOHAWKWGY	MOHAWKWY
SB SAFETY FOOTWEAR REQUIREMENT	<b>~</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>								
COMPLIES TO EN ISO 20345:2011	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>									
COMPLIES TO AS 2210.3:2019	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>~</b>									
ВМР	<b>@</b>	<b>@</b>	<b>@</b>													
SB P ANTI-PENETRATION	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>				<b>✓</b>		<b>✓</b>						
SLIP RESISTANCE SRC/SRB	SRC	SRC	SRC	SRC	SRB	SRC	SRC	SRB	SRC	SRB	SRB	SRC	SRC	SRC	SRC	SRC
S1 ANTI-STATIC									<b>✓</b>			<b>✓</b>				
EH ELECTRICAL HAZARD	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>									<b>✓</b>			
HEAT RESISTANCE SOLE 150°C/300°C	300°C	300°C	300°C	300°C	150°C	150°C	150°C	150°C	150°C	150°C	150°C	150°C	300°C	150°C	150°C	150°C
TOECAP (STEEL)	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>									
OIL RESISTANT SOLE	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>									
ACID RESISTANT SOLE	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>									
WATER RESISTANT UPPER (WRU)	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>									
ENERGY ABSORPTION (E)	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>												
ULTRA-WIDE FIT SIZES 8W-12W	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>												