

CONFINED SPACE ENTRY TRIPOD

DESCRIPTION

Confined Space Entry Tripod

Part Code: HSTP29

The LINQ Confined Space Tripod is lightweight and portable. Made from aluminium, LINQ tripods can move easily from one job to another and can be setup by one person. Adjustable legs come with pins and a safety chain to ensure secure placement when in position. The LINQ tripod head provides dual anchorage points to allow for backup systems to be used. Locking pins provide a further safety feature by ensuring the winch wire rope sits securely in the pully and to also secure the tripod frame in place once setup and ready for work.

FEATURES & BENEFITS

- Lightweight and portable for ease of setup by one person
- Telescopic legs allow height adjustment for increased versatility, comes with locking pins attached by cable
- Comes with mounting bracket for LINQ rescue winch
- Dual anchorage points rated at 12kN
- Comes with safety chain for secure placement of legs
- Twin mounted pulleys in the tripod head for prolonged guiding of the winch cable through the main leg
- Steel supported feet with rubber sole increases friction assisting in slippery environments and provides stability

PRODUCT DETAILS

- Weight: 16.8kg ± 10gm
- Adjustable height between 1.9 2.9M
- At minimum height distance between legs: 1.2m
- At maximum height distance between legs: 1.8m
- Lifting load capacity: 500kg

TECHNICAL INFORMATION

- Static strength: Both eye anchorages tested at 12kN for 3 minutes
- Dynamic strength and integrity test: When tested dynamically with a rigid mass of 100kg, the test mass shall be arrested, and anchor hold an increased mass of 300kg for 3 minutes
- Corrosion protection: Corrosion test in accordance with ISO 9227:2012; 24 hours neutral salt spray, followed by a further 24 hours salt spray. No visual evidence of any rust damage present



STANDARDS

Conforms to standard EN375:2012

Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.



CONFINED SPACE ENTRY TRIPOD: ACCESSORIES



- Tested load: 1350kg
- · Rated load: 135kg
- Maximum lifting: 25M



- Steel construction
- Easy to fit



- Replacement of your existing bag when required
- Carry straps for better mobility

TRIPOD REMOVABLE BRACKET for IRSR10R

- TRBM10



- Steel construction
- Easy fit design



TRIPOD REMOVABLE BRACKET for IRSR2OR

- TRRM20



- Steel construction
- Easy fit design



TRIPOD REMOVABLE BRACKET for IRSR3OR

- TRBM30



- Steel construction
- Easy fit design



SELF RETRACTING TYPE 3 LOQ-BLOQ with RETRIEVAL FUNCTION