

# Hardcap Aerolite<sup>®</sup>

AAF000-001-1AN / AAF000-002-1AN / AAG000-001-1AN / AAG000-002-1AN



## Short Peak (50mm)



Black | AAF000-001-1AN

Navy | AAF000-002-1AN

## Micro Peak (25mm)





Black | AAG000-001-1AN



### DESCRIPTION

The HardCap AeroLite<sup>®</sup> is the lightest full shell bump cap available on the market weighing less than 135g without compromising on performance.

A direct evolution of the popular HardCap A1+<sup>™</sup>, the HardCap AeroLite<sup>®</sup> represents the forefront of innovation within the JSP<sup>®</sup> head protection range, providing complete protection in its category.

### FEATURES

- Underneath the sleek textile cover is a tough HDPE shell and a lightweight EPP impact liner, carefully designed to allow for flexibility and comfort for the wearer.
- Replaceable padding to provide extra comfort and a better fit. The comfort pad and sweatband are moisture wicking to move sweat away from the skin.
- The cover has large open weave panels allowing the easy transfer of cool air. This substantially reduces heat build-up and discomfort for the wearer, especially when worn over long periods.
- Get your logo embroidered onto the front or back of your HardCap Aerolite<sup>®</sup>.

- Large reflective areas on the side panels of the cover and reflective piping around the peak provide extra visibility and improved safety in lowlight conditions.
- Available in black or navy, with either a 50mm or 25mm peak. The longer peak provides better shade and the shorter peak provides improved vision when looking upward.
- The cover is removable and machine washable. The sweatband and padding are treated with Polygiene<sup>®</sup>, which reduces skin irritations, odours and wash cycles, and prolongs the lifetime of the Embroidery Logos fabrics.
- Heat transfer your logo onto either the front, back or side of your HardCap Aerolite.



AUSTRALIA TECH SUPPORT: 1300 275 820 CUSTOMER SERVICE: 1300 770 723

NEW ZEALAND TECH SUPPORT: 0800 888 778 CUSTOMER SERVICE: 0800 888 778

PIPANZ.COM EMAIL: INFO@PIPANZ.COM

## SAFETY STANDARDS

- EN 352-3EN 812
- ction

	<sup>Peak</sup> 5cm (short peak) 2.5cm (micro peak)		Impact Resistance 12 Joules x 4
☀	Maximum Temperature +50°C		Minimum Temperature -40°C
HDPE	HDPE Shell Yes	R A	Recyclable Shell
	Slip Ratchet Slip		Ventilation Yes
€66	Reflective Option Standard	Ø	Anti-bacterial Coating Polygiene®
bsi	BSI Kitemark <b>Yes</b>	X°C	Machine Washable At Max 30°C
	Product Weight 127g	$\bigcirc$	Optional 2 Point chinstrap (EN397 & EN 812 compliant) Optional
¢	Size 53-64cm		

## APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Aerospace	Agricultural	
Airports	Construction and Infrastructure	
Facilities Management	Food and Drink Manufacturing	
Hospitals, Healthcare & Pharmaceuticals	Law Enforcement	
Manufacturing	Maritime	
Oil, Gas, and Chemical Companies	Rail and Tunnelling	
Renewable, Wind and Solar Energy	Sole Trader	
Utilities Contractors		



AUSTRALIA TECH SUPPORT: **1300 275 820** CUSTOMER SERVICE: **1300 770 723**  NEW ZEALAND TECH SUPPORT: 0800 888 778 CUSTOMER SERVICE: 0800 888 778

PIPANZ.COM Email: INFO@PIPANZ.COM