

PROTECTIVE HEADWEAR



EVOGuard®C2 Industrial Visor

ADA250-060-000



DESCRIPTION

EVOGuard®C high performance industrial visors provide comprehensive facial coverage without limiting movement. The optical class 1 visor range offers UV protection and a panoramic view with minimal distortion.

Fully compatible with EVOGuard® browguard systems and *EVO® helmet models, the C2 visor offers up to AT rated impact protection and is also suitable for use with the Force®8 half mask and P3 filters.

*Excluding EVO®6100 and EVO® VISTA® ranges.

SAFETY STANDARDS

ANSI Z87. 1
AS/NZS 1337

FEATURES

- EVOGuard® visors maximise compatibility with JSP half masks, disposable respirators, prescription glasses and the Sonis® helmet mounted ear defender range.
- High performance visor offering up to A rated impact resistance when fitted to a safety helmet and medium energy impact protection with the EVOGuard® browguard.
- Visor filters harmful UV radiation to protect the eyes whilst also offering high light transmission and enhanced colour recognition.
- The optical class 1 visor offers a panoramic view with minimal distortion, ideal for comfortable all day wear.
- EVOGuard® visors provide comprehensive facial coverage without limiting movement.
- Compatible with EVO® helmet models and EVOGuard® browguard systems. Visor supplied with dual system clips for mounting to a helmet or browguard.

SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN
filtering effect Scale Number
2C



Manufacturer's Trademark
JSP Dagger



High Energy Impact resists a 6 mm, 0.86g ball
@ 190 m/s Maximum protection for face shields
A - When Fitted to EVO® Helmet



The letter T, immediately after the mechanical
strength symbol, authorises use for high speed
particles at extreme temperatures. (-5°C and
+55°C) Optional
T



Resistance to Molten Metals and Hot Solids
Helmets (optional)
9



Resistance to fogging (optional)
N



BSI Kitemark
Yes



Product Weight
185g



Kit
Supplied With: EVO® 2,3,5,DS, Lite, Skyworker™
Arms. EVO8/EVOLite Badgeholder Arms.
EVOGuard® Browguard Mounting System.



LIGHT TRANSMISSION BREAKDOWN Lens
Shade number
1.2



Optical Class (1 – Class 1 – High quality for
regular use. 2 – Class 2 – Medium quality for
occasional use. 3 – Class 3 – Low quality for
exceptional use)
1



Medium Energy Impact resists a 6 mm, 0.86g
ball @ 120 m/s Maximum protection for goggles.
B - When Fitted To EVOGuard® Browguard



Protection from Liquid Splash
3



Resistance to Surface Damage by Fine Particles
(optional)
K



Visor Length
18.5cm

Material
Polycarbonate Shield



Recyclable
Yes

APPLICATIONS

Aerospace	Agricultural
Airports	Construction and Infrastructure
Facilities Management	Food and Drink Manufacturing
Law Enforcement	Manufacturing
Maritime	Mining, Aggregates and Quarrying
Oil, Gas and Chemical Companies	Rail and Tunnelling
Renewable, Wind and Solar Energy	Scaffolding and Roofing
Sole Trader	Utilities Contractors