# **KARABINER TRIPLE ACTION - STEEL**



The LINQ range of karabiners offer exceptional strength, manufactured under stringent quality control conditions. The triple action self-closing mechanism is designed to reduce the probability of involuntary opening or release. High strength steel construction provides robust and safe connection.

#### **PRODUCT FEATURES** >

- High tensile drop forged steel.
- Triple action and self-closing mechanism.
- Sleek design minimises snagging and damage to harness and lanyard webbing.
- >6kN gate strength. Top and side.
- Stringent ISO 10333-5 batch testing conducted to international standards.
- Black electrophoresis finish.

## PRODUCT DETAILS >

- · Opening: 26mm
- Weight: 261gm
- MBS: 30kN
- Gate: 6kN
- Width: 85mm
- Length: 112mm

#### **APPLICATIONS** >

Multiple applications: Agricultural, Chemical, Construction, Manufacturing, Mining Oil and Gas, Transportation, Utilities, Marine.

## STANDARDS >

Conforms to and accepted under AS 1891.5:2020. Min gate strength requirement of >6kN.



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice\* If in doubt please contact the LINQ helpline.

LINOHS.COM

PARAMOUNTSAFETY.COM

PARAMOUNT SAFETY PRODUCTS AUSTRALIA 12 FELLOWSHIP ROAD, GNANGARA, WA 6077 TECH SUPPORT: 1300 546 747 CUSTOMER SERVICE: 1300 770 723 EMAIL: INFO@PARAMOUNTSAFETY.COM PARAMOUNT SAFETY PRODUCTS NEW ZEALAND 7 SIR WOOLF FISHER DRIVE, HIGHBROOK, EAST TAMAKI, AUCKLAND 2013 TECH SUPPORT: 0800 546 747 CUSTOMER SERVICE: 0800 888 778 EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ



