

DOUBLE ACTION SNAP HOOK - STEEL



PART CODE: **HSSNH**

The LINQ range of hooks offer exceptional strength, manufactured under stringent quality control conditions. The HSSNH Snap Hook is double action, requiring two distinctive easy to operate actions to open the gate. High strength steel construction provides robust and safe connection.

PRODUCT FEATURES >

- High tensile, drop forged steel.
- Smooth edging preventing snags on the job.
- Easily operated using one hand.
- Double action and self-closing mechanism.
- 16kN gate strength. Top and side.
- Stringent ISO 10333-5 batch testing conducted to international standards.

PRODUCT DETAILS >

- **Opening:** 19mm
- **Weight:** 375gm
- **MBS:** 25kN
- **Gate:** 16kN
- **Width:** 66mm
- **Length:** 149mm

APPLICATIONS >

Scaffolding, Mining, Maintenance, Marine.
Any work requiring the use of a larger gate opening.

STANDARDS >

Certified to ANSI Z359.12, CSA Z259.12.
Conforms to and accepted under AS 1891.5:2020.
Min gate strength requirement of >6kN.



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice If in doubt please contact the LINQ helpline.*

PARAMOUNT SAFETY PRODUCTS AUSTRALIA
12 FELLOWSHIP ROAD,
GNANGARA, WA 6077
TECH SUPPORT: 1300 546 747
CUSTOMER SERVICE: 1300 770 723
EMAIL: INFO@PARAMOUNTSAFETY.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND
7 SIR WOOLF FISHER DRIVE, Highbrook,
EAST TAMAKI, AUCKLAND 2013
TECH SUPPORT: 0800 546 747
CUSTOMER SERVICE: 0800 888 778
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

LINQHS.COM
PARAMOUNTSAFETY.COM

 **HEIGHT
SAFETY**
FROM
**PARAMOUNT
SAFETY PRODUCTS**