

ESSENTIAL QR STANDARD ROOFERS KIT

PART CODE: **KITRSTDQR**



**HEIGHT
SAFETY**

PRODUCT INFORMATION >

The LINQ Standard Roofers Kit has been designed to meet the general requirements of workers who are working at heights. The kit offers exceptional value for money as opposed to buying the items individually. If your site has specific requirements, LINQ also offers a custom kit service. Customers can take advantage of the LINQ custom kit service by tailoring a kit to suit the needs of their individual work site, choosing from any LINQ harnesses, lanyards, ropes, karabiners and accessories.



KIT INCLUDES >

KSGA18: 2 x Screw Gate Karabiner

- Opening: 18mm
- Weight: 165gm
- Rating: 25kN
- Width: 58mm
- Length: 110mm



HSASE2515: Anchor Strap Endless

- 25mm - 1.5M
- Rated to 22kN



WL01SNSN: Shock Absorbing Webbing Lanyard Single Hook 2X SNAP HOOK

- Batch tested to AS/NZS 1891.1: 3.8m drop using 100kg test weight, reducing forces to under 4.5kN
- An exclusive Extended Length Energy Absorber (ELEA) designed to protect a worker, of up to 150kg, tools and equipment
- Drop forged lanyard hardware for added strength in case of extreme conditions
- Contrast stitch thread colour for easy inspection and AS/NZS 1891.1 compliance



RKRG015: 15M Kernmantle Rope C/W Rope Grap & Thimble Eye

- Kernmantle rope exceeds 14.7kN
- 12mm thickness +/-
- 110gm of polyester as opposed to 65gm. This results in exceptional strength capabilities
- Rope grab as per restraint technique, in order to ensure stopping force is less than 6kN, rope grab should always be used in conjunction with a shock absorbing element



H101QR: Essential Harness with quick release padded buckles

- Pebble Weave Webbing design provides maximum grip for buckles, eliminating webbing slippage and the need for continual re-adjustment.
- Retro-Reflective Thread in webbing for improved visibility in low light.
- Sub Pelvic Strap integration along the line of Belay Loops, places the worker away from hardware in the event of a fall, significantly reducing the risk of injury from hardware hitting the worker.
- Articulated Chest Strap and shoulder adjustment points, designed for additional user comfort and female users, due to lower positioning of strap.
- Stitch Pattern: THETA Pattern combines 313 stitches to exceed 28kN of strength; AS/NZ compliant colour contrast



AS/NZS 1891.1:2020
BMP 713822
BMP 713823
Australian Standard



**WORKING AT
HEIGHT ASSOCIATION**
REACHING NEW LEVELS IN SAFETY

Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice. If in doubt please contact the LINQ helpline.

AUS: 1300 546 747

NZ: 0800 546 747

INTERNATIONAL: +61 1300 546 747

WWW.LINQHS.COM