



* Locate where the front and back torso webbing intersect at the hip – known as pelvic crossover.









Insert the strap, as shown, between the harness pelvic crossover webbing sections.







STEP 2

Feed the buckle through the buckle strap, as shown.

STEP 3

Continue to feed the buckle through the strap, as shown, so as to create a choker set up for the buckle.





The buckle should hang down through the loop of the strap so that it can be easily accessed in the event of a suspension fall incident.











Insert the bottom strap of the trauma pack, as shown.







STEP 2

Once the bottom strap has been threaded, as shown, fold the pack into and through the loop on the pouch.











Once the pack has been threaded through its own loop, locate the elastic strap on the pack and thread the harness leg through this loop, as shown, so that the pack can be easily accessed and does not flop about.



Adjust the pack for comfort and for ease of location.





USER GUIDE









When suspended after a fall, locate the trauma pack and pull the zipper so as to release the trauma strap.









Once the pack has been released from the one side, locate the female buckle and then insert the male buckle, as shown.







STEP 3

Once the two buckles are co-joined, adjust the length of the strap to a length that will allow you to stand into the strap, so as to relieve the pressure of your body on the leg straps of the harness.

It is recommended that a wearer should practice trauma strap deployment so as to familiarise yourself with the actions needed in the event of a fall incident.

AUSTRALIA - 1300 LINQ HS (5467 47) NEW ZEALAND - 0800 LINQ HS (5467 47) WWW. LINQHS .COM