PRATT CLASS 4 DANGEROUS GOODS STORAGE CABINET: 60L - 1 DOOR - 2 SHELVES

PRATT INDOOR CLASS 4 STORAGE CABINETS COMPLY WITH THE STANDARD AS/NZS5026 "THE STORAGE AND HANDLING OF CLASS 4 DANGEROUS GOODS".

This range of cabinets is for the storage of Class 4 chemicals in liquid or solid form as classified by the United Nations criteria and the ADG Code for Dangerous Goods. Please refer to the Standard. These include the following divisions: Flammable Solids, Spontaneously or Combustible Dangerous when wet.

FEATURES & BENEFITS:

- Constructed of double walled 1.2mm thick galvanised steel.
- Self closing door with speed adjustable hydraulic closure.
- 2 x 1.6mm thick, perforated, galvanised steel shelf.
- Continual piano type door hinge.
- Overlapping door edging to prevent ingress of heat.
- Adjustable shelf heights at 45mm increments.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- Magnetic catch to hold door in closed position to provide automatic release in the event of pressure build up.
- Recessed non lockable handle.
- External static earth connection and 1 x bonding wire.
- Solvent resistant yellow baked powder coated finish.
- 150mm deep liquid tight sump.
- Palletised and packaged with strong cardboard for protection during transportation and storage.
- Either Flammable Solid, Spontaneously Combustible or Dangerous When Wet diamonds and other decals supplied.
- Optional additional shelves available.
- Includes set of rubber feet.

- WEIGHT: 62kg 60L - CAPACITY: - DOORS:

- SHELVES: 2 (Inc. Base Level)

- EXTRASHELF: 5517-29S











VOLUME CAPACITY	PER SHELF	TOTAL
2L Winchester	6	12
4L Winchester	4	8
4L Round Can	4	8
20L Round Can	1	2

EXTERNAL (MM)		INTERNAL (MM)			
HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH
1065	515	465	820	420	370

NUTE:

1. INTERNAL HEIGHT IS TAKEN FROM THE TOP OF THE SUMP SILL/BOTTOM SHELF TO THE CEILING.

2. FOR TOTAL EXTERNAL WIDTH MEASUREMENT, ADD 6MM PER VENT BUNG FOR TIGHT
CLEARANCE LOCATIONS.

3. AS/NZS 5026 SPECIFIES A MAXIMUM OF 25KG OR L FOR CATEGORY A, 50KG OR L OF CATEGORY B OR 100KG

OR LOF CATEGORY C. CLASS 4 CHEMICALS, OTHER CAPACITY LIMITATIONS DO APPLY