PRATT OXIDIZING AGENT STORAGE CABINET: **160L - 2 DOORS - 2 SHELVES**

PRATT INDOOR OXIDIZING AGENT STORAGE CABINETS **COMPLY WITH THE AUSTRALIAN STANDARD AS4326** "THE STORAGE AND HANDLING OF OXIDIZING AGENTS".

This range of cabinets is for the storage of Oxidizing Agents in liquid or solid as classified by the United Nations criteria and the ADG Code for Dangerous Goods. These include chemicals such as: Hypochlorite-inorganic, Hydrogen Peroxide, Perchlorites-inorganic, Potassium Nitrate etc.

FEATURES & BENEFITS:

- Constructed of double walled 1.2mm thick galvanised steel.
- 2 x sequential self closing doors fitted with speed adjustable hydraulic closures.
- 2 x 1.6mm thick, perforated, galvanised steel shelf.
- Continual piano type door hinge.
- Overlapping door edging to prevent ingress of heat.
- Adjustable shelf heights at 45mm increments.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- Magnetic catches to hold doors in closed position to provide automatic release in the event of pressure build up.
- Recessed non lockable handles.
- External static earth connection and 1 x bonding wire.
- Solvent resistant yellow baked powder coated finish.
- 150mm deep liquid tight sump.
- Palletised and packaged with strong cardboard for protection during transportation and storage.
- Oxidizing Agent diamond and other decals applied.
- Optional additional shelves available.
- Includes set of rubber feet.
- WEIGHT: 141kg
- CAPACITY: 160L
- 2 - DOORS:
- SHELVES: 2 (Inc. Base Level)
- EXTRA SHELF: 5545-29S

E	XTERNAL (MN	1)	11	NTERNAL (MM	1)
HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH
1295	1115	500	1015	1020	415

NOTE

1. INTERNAL HEIGHT IS TAKEN FROM THE TOP OF THE SUMP SILL/BOTTOM SHELF TO THE CEILING. 2. FOR TOTAL EXTERNAL WIDTH MEASUREMENT, ADD 6MM PER VENT BUNG FOR TIGHT

CLEARANCE LOCATIONS. 3. AS 4326 SPECIFIES A MAXIMUM OF 50KG OR L FOR PACKAGING GROUP I OXIDIZING AGENTS.

PARAMOUNT SAFETY PRODUCTS AUSTRALIA 12 FELLOWSHIP ROAD,

GNANGARA, WA 6077 TECH SUPPORT: 1300 133 226 CUSTOMER SERVICE: 1300 133 226 EMAIL: INFO@PRATTSAFETY.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND 7 SIR WOOLF FISHER DRIVE, HIGHBROOK, EAST TAMAKI, AUCKLAND 2013 TECH SUPPORT: 0800 888 778 **CUSTOMER SERVICE: 0800 888 778** EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ





VOLUME CAPACITY	PER SHELF	TOTAL
2L Winchester	14	28
4L Winchester	12	24
4L Round Can	10	20
20L Round Can	3	6



PRATTSAFETY.COM PARAMOUNTSAFETY.COM