

# PRATT FLAMMABLE LIQUID STORAGE CABINET: 60L - 1 DOOR - 2 SHELVES

**PRATT INDOOR FLAMMABLE LIQUID STORAGE CABINETS COMPLY WITH THE AUSTRALIAN STANDARD AS 1940 "THE STORAGE & HANDLING OF FLAMMABLE & COMBUSTIBLE LIQUIDS".**

This cabinet is suitable for the storage of flammable or combustible liquids as classified by the United Nations criteria and the ADG Code for Dangerous Goods. For example: petrol, diesel, paints, solvents, thinners, kerosene, turpentine, white spirits, alcohol and ethanol etc. They are also suitable for the storage of aerosols where additional fire protection is required.

## FEATURES & BENEFITS:

- Constructed of double walled 1.2mm thick galvanised steel.
- Self closing door with speed adjustable hydraulic closure.
- 2 x 1.6mm thick, perforated, galvanised steel shelves.
- Continual stainless steel piano type door hinge.
- Overlapping door edging to prevent ingress of heat.
- Adjustable shelf heights at 45mm increments.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- 3 point self latching door mechanism.
- Recessed handle with keyed alike lock with 2 keys.
- External static earth connection and 1 x earthing wire.
- Solvent resistant yellow baked powder coated finish.
- 150mm deep liquid tight sump.
- Palletised and packaged with strong cardboard for protection during transportation and storage.
- Flammable Liquid diamond and other decals applied.
- Optional additional shelves available.
- Includes set of 4 rubber feet.

- **WEIGHT:** 62kg
- **CAPACITY:** 60L
- **DOORS:** 1
- **SHELVES:** 2 (Inc. Base Level)
- **EXTRA SHELF:** 5517-29S



| EXTERNAL (MM) |       |       | INTERNAL (MM) |       |       |
|---------------|-------|-------|---------------|-------|-------|
| HEIGHT        | WIDTH | DEPTH | HEIGHT        | WIDTH | DEPTH |
| 1065          | 515   | 465   | 820           | 420   | 370   |

NOTE:  
1. INTERNAL HEIGHT IS TAKEN FROM THE TOP OF THE SUMP SILL/BOTTOM SHELF TO THE CEILING.  
2. FOR TOTAL EXTERNAL WIDTH MEASUREMENT, ADD 6MM PER VENT BUNG FOR TIGHT CLEARANCE LOCATIONS.

| VOLUME CAPACITY | PER SHELF | TOTAL |
|-----------------|-----------|-------|
| 2L Winchester   | 6         | 12    |
| 4L Winchester   | 4         | 8     |
| 4L Paint Can    | 4         | 8     |
| 20L Round Can   | 1         | 2     |