PRATT CLASS 4 DANGEROUS GOODS STORAGE CABINET: **160L - 2 DOORS - 2 SHELVES**

PRATT INDOOR CLASS 4 STORAGE CABINETS COMPLY WITH THE STANDARD AS/NZS5026 "THE STORAGE AND HANDLING OF CLASS 4 DANGEROUS GOODS".

This range of cabinets is for the storage of Class 4 chemicals in liquid or solid form as classified by the United Nations criteria and the ADG Code for Dangerous Goods. Please refer to the Standard. These include the following divisions: Flammable Solids, Spontaneously or Combustible Dangerous when wet.

FEATURES & BENEFITS:

- Constructed of double walled 1.2mm thick galvanised steel.
- 2 x sequential self closing doors fitted with speed adjustable hydraulic closures.
- 2 x 1.6mm thick, perforated, galvanised steel shelf.
- Continual piano type door hinge.
- Overlapping door edging to prevent ingress of heat.
- Adjustable shelf heights at 45mm increments.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- Magnetic catches to hold doors in closed position to provide automatic release in the event of pressure build up.
- Recessed non lockable handles.
- External static earth connection and 1 x bonding wire.
- Solvent resistant yellow baked powder coated finish.
- 150mm deep liquid tight sump.
- Palletised and packaged with strong cardboard for protection during transportation and storage.
- Either Flammable Solid, Spontaneously Combustible or Dangerous When Wet diamonds and other decals applied.
- Optional additional shelves available.

-	WEIGHT:	141kg
---	---------	-------

- 160L - CAPACITY:
- DOORS:
- 2 2 (Inc. Base Level) - SHELVES:
- 5545-29S - EXTRA SHELF:

E	EXTERNAL (MM)		INTERNAL (MM)		
HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH
1295	1115	500	1015	1020	415

NUTE: 1. INTERNAL HEIGHT IS TAKEN FROM THE TOP OF THE SUMP SILL/BOTTOM SHELF TO THE CEILING. 2. FOR TOTAL EXTERNAL WIDTH MEASUREMENT, ADD 6MM PER VENT BUNG FOR TIGHT CLEARANCE LOCATIONS. 3. AS/NZS 5026 SPECIFIES A MAXIMUM OF 25KG OR L FOR CATEGORY A, 50KG OR L OF CATEGORY B OR 100KG

OR LOF CATEGORY C. CLASS 4 CHEMICALS, OTHER CAPACITY LIMITATIONS DO APPLY

PARAMOUNT SAFETY PRODUCTS AUSTRALIA 12 FELLOWSHIP ROAD,

GNANGARA, WA 6077 TECH SUPPORT: 1300 133 226 CUSTOMER SERVICE: 1300 133 226 EMAIL: INFO@PRATTSAFETY.COM

PARAMOUNT SAFETY PRODUCTS NEW 7FALAND 7 SIR WOOLF FISHER DRIVE, HIGHBROOK, EAST TAMAKI, AUCKLAND 2013 TECH SUPPORT: 0800 888 778 **CUSTOMER SERVICE: 0800 888 778** EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

VOLUME CAPACITY	PER SHELF	TOTAL
2L Winchester	14	28
4L Winchester	12	24
4L Round Can	10	20
20L Round Can	3	6



MAX CAPACITY CUSTOMER SERVICE 1300 133 226

NO SMOKING

NO IGNITION SOURCES

WITHIN 3m

PRATTSAFETY.COM PARAMOUNTSAFETY.COM