PRATT CLASS 4 DANGEROUS GOODS STORAGE CABINET: 100L - 2 DOORS - 1 SHELF

PRATT INDOOR CLASS 4 STORAGE CABINETS COMPLY WITH THE STANDARD AS/NZS5026 "THE STORAGE AND HANDLING OF CLASS 4 DANGEROUS GOODS".

This range of cabinets is for the storage of Class 4 chemicals in liquid or solid form as classified by the United Nations criteria and the ADG Code for Dangerous Goods. Please refer to the Standard. These include the following divisions: Flammable Solids, Spontaneously or Combustible Dangerous when wet.

FEATURES & BENEFITS:

- Low profile under bench design.
- Constructed of double walled 1.2mm thick galvanised steel.
- 2 x sequential self closing doors fitted with speed adjustable hydraulic closures.
- 1 x 1.6mm thick, perforated, galvanised steel shelf.
- Continual piano type door hinge.
- Overlapping door edging to prevent ingress of heat.
- Adjustable shelf heights at 45mm increments.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- Magnetic catches to hold doors in closed position to provide automatic release in the event of pressure build up.
- Recessed non lockable handles.
- External static earth connection and 1 x bonding wire.
- Solvent resistant yellow baked powder coated finish.
- 150mm deep liquid tight sump.
- Palletised and packaged with strong cardboard for protection.
- Either Flammable Solid, Spontaneously Combustible or Dangerous When Wet diamonds and other decals supplied.
- Optional additional shelves available.
- Includes set of rubber feet.

- WEIGHT: 100kg - CAPACITY: 100L - DOORS:

1 (Inc. Base Level) - SHELVES:

- EXTRA SHELF: 5535-29S

	SPONTANEOUSLY COMBUSTIBLE	NO SMOKING No ignition sources Within 3m
· 📵	4	
	MAX CAPACITY 100 Litres CAPACITY 100 Litres 1000 133 226	







EXTERNAL (MM)			INTERNAL (MM)		
HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH
770	935	620	495	840	530

NUTE:

1. INTERNAL HEIGHT IS TAKEN FROM THE TOP OF THE SUMP SILL/BOTTOM SHELF TO THE CEILING.

2. FOR TOTAL EXTERNAL WIDTH MEASUREMENT, ADD 6MM PER VENT BUNG FOR TIGHT
CLEARANCE LOCATIONS.

3. AS/NZS 5026 SPECIFIES A MAXIMUM OF 25KG OR L FOR CATEGORY A, 50KG OR L OF CATEGORY B OR 100KG

OR LOF CATEGORY C. CLASS 4 CHEMICALS, OTHER CAPACITY LIMITATIONS DO APPLY

VOLUME CAPACITY	PER SHELF	TOTAL
2L Winchester	18	18
4L Winchester	15	15
4L Round Can	12	12
20L Round Can	4	4