PRATT CLASS 4 DANGEROUS GOODS STORAGE CABINET: 250L - 2 DOORS - 3 SHELVES

PRATT INDOOR CLASS 4 STORAGE CABINETS COMPLY WITH THE STANDARD AS/NZS5026 "THE STORAGE AND HANDLING OF CLASS 4 DANGEROUS GOODS".

This range of cabinets is for the storage of Class 4 chemicals in liquid or solid form as classified by the United Nations criteria and the ADG Code for Dangerous Goods. Please refer to the Standard. These include the following divisions: Flammable Solids, Spontaneously or Combustible Dangerous when wet.

FEATURES & BENEFITS:

- Constructed of double walled 1.2mm thick galvanised steel.
- 2 x sequential self closing doors fitted with speed adjustable hydraulic closures.
- 3 x 1.6mm thick, perforated, galvanised steel shelves.
- Continual piano type door hinge.
- Overlapping door edging to prevent ingress of heat.
- Adjustable shelf heights at 90mm increments.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- Magnetic catches to hold doors in closed position to provide automatic release in the event of pressure build up.
- Recessed non lockable handles.
- External static earth connection and 1 x bonding wire.
- Solvent resistant yellow baked powder coated finish.
- 150mm deep liquid tight sump.
- Palletised and packaged with strong cardboard for protection during transportation and storage.
- Either Flammable Solid, Spontaneously Combustible or Dangerous When Wet diamonds and other decals supplied.
- Optional additional shelves available.

- WEIGHT:	185kg
-----------	-------

- CAPACITY: 250L
- DOORS:
- 2 3 (Inc. Base Level) - SHELVES:
- 5545-29S - EXTRA SHELF:

EXTERNAL (MM)		11	NTERNAL (MM	1)	
HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH
1825	1115	500	1545	1020	415

NUTE: 1. INTERNAL HEIGHT IS TAKEN FROM THE TOP OF THE SUMP SILL/BOTTOM SHELF TO THE CEILING. 2. FOR TOTAL EXTERNAL WIDTH MEASUREMENT, ADD 6MM PER VENT BUNG FOR TIGHT CLEARANCE LOCATIONS. 3. AS/NZS 5026 SPECIFIES A MAXIMUM OF 25KG OR L FOR CATEGORY A, 50KG OR L OF CATEGORY B OR 100KG

OR LOF CATEGORY C. CLASS 4 CHEMICALS, OTHER CAPACITY LIMITATIONS DO APPLY

PARAMOUNT SAFETY PRODUCTS AUSTRALIA 12 FELLOWSHIP ROAD,

GNANGARA, WA 6077 TECH SUPPORT: 1300 133 226 CUSTOMER SERVICE: 1300 133 226 EMAIL: INFO@PRATTSAFETY.COM

PARAMOUNT SAFETY PRODUCTS NEW 7FALAND 7 SIR WOOLF FISHER DRIVE, HIGHBROOK, EAST TAMAKI, AUCKLAND 2013 TECH SUPPORT: 0800 888 778 **CUSTOMER SERVICE: 0800 888 778** EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

	DANGEROUS WHEN WET 4	NO SMOKING No Ignition Sources Within 3m
· 🐑	MAX CAPACITY 250 Litres Catal Control Source Catal Control Source	



VOLUME CAPACITY	PER SHELF	TOTAL
2L Winchester	14	42
4L Winchester	12	36
4L Round Can	10	30
20L Round Can	3	9



PRATTSAFETY.COM PARAMOUNTSAFETY.COM