PRATT FLAMMABLE LIQUID STORAGE CABINET: 350L - 2 DOORS - 3 SHELVES

PRATT INDOOR FLAMMABLE LIQUID STORAGE **CABINETS COMPLY WITH THE AUSTRALIAN STANDARD** AS 1940 "THE STORAGE & HANDLING OF FLAMMABLE & COMBUSTIBLE LIQUIDS".

This cabinet is suitable for the storage of flammable or combustible liquids as classified by the United Nations criteria and the ADG Code for Dangerous Goods. For example: petrol, diesel, paints, solvents, thinners, kerosene, turpentine, white spirits, alcohol and ethanol etc. They are also suitable for the storage of aerosols where additional fire protection is required.

FEATURES & BENEFITS:

- Constructed of double walled 1.2mm thick galvanised steel.
- 2 x sequential self closing doors fitted with speed adjustable hydraulic closures.
- 3 x 1.6mm thick, perforated, galvanised steel shelves.
- Continual stainless steel piano type door hinge.
- Overlapping door edging to prevent ingress of heat.
- Adjustable shelf heights at 90mm increments.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- 3 point self latching door mechanism.
- Recessed handle with keyed alike lock with 2 keys.
- External static earth connection and 1 x earthing wire.
- Solvent resistant yellow baked powder coated finish.
- 150mm deep liquid tight sump.
- Palletised and packaged with strong cardboard for protection during transportation and storage.
- Flammable Liquid diamond and other decals applied.
- Optional additional shelves available.

- WEIGHT: 230kg 350L - CAPACITY: - DOORS:

3 (Inc. Base Level) - SHELVES:

5560-29S - EXTRA SHELF:







EXTERNAL (MM)			INTERNAL (MM)			
HEIGH	Т	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH
1825		1440	585	1545	1350	495

NOTE:

1. FOR ALL TWO DOOR CABINETS, THE INTERNAL HEIGHT IS TAKEN FROM THE TOP OF SUMP SILL/BOTTOM SHELF TO THE SEQUENTIAL CHASSIS ASSEMBLY.

2. FOR TOTAL EXTERNAL WIDTH MEASUREMENT, ADD 6MM PER VENT BUNG FOR TIGHT

CLEARANCE LOCATIONS.

VOLUME CAPACITY	PER SHELF	TOTAL	
2L Winchester	30	90	
4L Winchester	16	48	
4L Paint Can	14	42	
20L Round Can	4	12	



T: 1300 133 226 E: INFO@PRATTSAFETY.COM.AU AUSTRALIA NEW ZEALAND T: 0800 133 226 E: INFO@PRATTSAFETY.CO.NZ INTERNATIONAL W: PRATTSAFETY.COM E: INFO@PRATTSAFETY.COM