

## PRATT ZEOLITE FLOOR SWEEP 15L / 30L PRODUCT CODE: FSZ15 / FSZ30

Zeolite is a mineral-based universal absorbent used to remove all liquid spills from hard surfaces such as concrete and bitumen. It is ideal when surfaces are weathered and porous. Use Zeolite Floor Sweep in windy conditions when a heavy, granular absorbent is required. Natural zeolite can successfully absorb spills of oil, fuel, coolants, paints, degreaser, and mild acid. In addition, it eliminates odors and toxic vapors caused by spills on contact. Also, zeolite has a strong framework and unlike clay products, does not break down when saturated.

## FEATURES AND BENEFITS:

- All natural heat sterilised mineral contains no chemicals.
- Exceeds EPA landfill leachate tests.
- Absorbs immediately on contact.
- Super absorbent capacity.
- It will not leach back absorbed fluids ecologically safe.
- Maintains strength integrity when fully absorbed reduces slippage and makes clean-up easy.
- Natural bonding action of zeolite makes it far more active in the absorption and absorption process.
- Particle size gradation designed to maximise absorption and minimise floor residue.
- De-Dusted to reduce surface bogging and improves handling.
- Strong wicking action to pull spills from the surface.

Material: Absorbent Zeolite Granules FSZ15: Dimensions: L:50cm x W:34cm x D:8cm Weight: 15L / 9.5kg FSZ30: Dimensions: L:80cm x W:35cm x D:12cm

Weight: 30L/20kg

## SUGGESTED STORAGE

Temperature: Between -10°C and 40°C. Humidity: Below 80%. Sunlight: Not to expose to direct sunlight.

## **INSTRUCTIONS FOR SPILL RESPONSE**

- STEP 1: Liberally spread Pratt Zeolite Floor Sweep over affected area.
- STEP 2: Firmly brush to effectively absorb all liquid.
- STEP 3: Dispose of used absorbents and spilt liquids in accordance with local laws.







AUSTRALIA T: 1300 133 226 E: info@prattsafety.com.au NEW ZEALAND T: 0800 133 226 E: info@prattsafety.co.nz