

# RESPIRATORY GEAR

## HORIZONTAL FLAT FOLD P2 RESPIRATOR WITH VALVE

PRODUCT DATA SHEET: PC2122



PRODUCT CODE:  
PC2122



### FEATURES AND BENEFITS

- Certified to AS/NZS 1716:2012 Respiratory Protective Devices.
- P2 disposable respirator for protection against mechanically & thermally generated particles.
- Dual latex free elastic straps for ease of donning & doffing.
- Horizontal flat fold for improved comfort & fit.
- Adjustable plastic nose bridge for enhanced seal.
- ProValve exhalation valve for decreased breathing resistance & heat stress.
- Easily worn with glasses & goggles.
- Resealable bag for hygienic storage.

### AVAILABLE IN

PRODUCT CODE	QUANTITY	CARTON
PC2122	12 pieces	20 boxes

### PRODUCT DETAILS

Straps:	Latex-Free Rubber Band
Staples:	Stainless
Nose Foam:	EVA
Nose Clip:	LLPDE
Filter Media:	Polypropylene Melt-Down
Weight:	16.2g ± 1

### CARE INSTRUCTIONS

Shelf life of the unopened product is 3 years from date of manufacture when stored within temperature range of -20°C to +25°C & less than 80% relative humidity.

Manufactured date printed onto filters, maximum life span is 6 months once filter is removed from original packaging, however life span is determined by the wearers ability to taste, smell or notice increase in breathing resistance.

Ensure mask is correctly fitted prior to each use & conduct annual fit testing in accordance with AS/NZS 1715:2009.



### WARNINGS AND USE LIMITATIONS

1. Facial hair has the potential to compromise the required protective seal of the respirator.
2. Ensure adequate oxygen levels are present.
3. Ensure the contamination is known and the respirator is suitable for the application.
4. Replace when taste, smell or the breathing resistance is high.
5. Store in a clean resealable storage device.

### STANDARDS

#### CERTIFIED TO:

AS/NZS 1716:2012 Respiratory Protective Devices  
Certified by Benchmark

To be used in conjunction with: AS/NZS 1715:2009 -  
Selection, use & maintenance of respiratory protective  
equipment



AS/NZS 1716:2012  
ID No: BMP547903

CLASSIFICATION	EFFICIENCY	EXAMPLE OF CONTAMINANTS/USES
P1	80% (Particles to 1µm micron = 0.001mm size)	Dust
P2	94% (particles to 0.3µm micron = 0.0003mm size)	Toxic dusts including asbestos, welding fumes
P3	99.95% (particles to <0.3µm micron = less than 0.0003mm size)	Toxic dusts including asbestos, welding fumes, full face and powered air performance at P3 only

### RELATED PRODUCTS

PRODUCT CODE:  
PCFFP2V



DUST MASKS FLAT FOLD  
P2+VALVE

PRODUCT CODE:  
PC822



DUST MASKS PROMESH  
P2+VALVE

PRODUCT CODE:  
FSPG531



FILTERSPEC REPLACEMENT  
DUST MASKS  
P2+VALVE+CARBON

PRODUCT CODE:  
PC321



DUST MASKS P2+VALVE

PRODUCT CODE:  
HMA1P2



ASSEMBLED HALF MASK  
WITH A1P2 FILTERS

AUSTRALIA:  
1800 770 723

ADELAIDE:  
(613) 9764 9900  
SA@PARAMOUNTSAFETY.COM.AU

MELBOURNE:  
(613) 9764 9900  
VIC@PARAMOUNTSAFETY.COM.AU

SYDNEY:  
(612) 9601 3877  
NSW@PARAMOUNTSAFETY.COM.AU

NEW ZEALAND:  
0800 770 723  
NZ@PARAMOUNTSAFETY.CO.NZ

BRISBANE:  
(617) 3806 2699  
QLD@PARAMOUNTSAFETY.COM.AU

PERTH:  
(618) 9301 7888  
WA@PARAMOUNTSAFETY.COM.AU

PROCHOICESAFETYGEAR.COM

