PROTECTIVE EYEWEAR PROTEUS 5 SAFETY GLASSES

PRODUCT DATA SHEET: 6600 | 6602









6602



FEATURES AND BENEFITS

- AquaShield Hardened Anti-Fog Technology
- Large Lens for increases lateral/horizontal eve coverage
- Foam Dust gasket and Strap available as standard inclusion
- SuperFlex arms ensure Low Clamp force reducing temporal pressure
- Cold Formable Arm for individual fit
- UV400 100% UV Protection on Tinted Lens
- Certified Medium Impact Protection

PRODUCT DETAILS

AS/NZS Medium Impact rated Lens Material:

Polycarbonate Base Curve 9

Frame/Arms: Polypropylene + TPR **Dust Gasket:** Polypropylene + EVA Foam

Weight: 34g without strap 42g with strap

Lens Coating AquaShield Hardened Anti-Fog Hydrophilic Technology

APPLICATIONS

The Pro Choice Safety Gear range of eye protection is ideal for protection against risks associated with a wide range of applications in both workplace and recreational environments. The Proteus Range of protective eyeware also incorporates excellent protection from dust and excellent integration with other PPE.

Typical applications include but are not limited to: Agriculture, aviation, automotive, chemical manufacturing, construction, forestry, heavy engineering, manufacturing, metal processing, mining and quarrying, transportation.

CLEANING INSTRUCTIONS

Clean with warm soapy water or mild lens cleaning solutions. Do not use alcohol based cleaning wipes/solutions as this may damage the lens coatings.

PARAMOUNT SAFETY PRODUCTS AUSTRALIA

12 FELLOWSHIP ROAD. GNANGARA, WA 6077 TECH SUPPORT: 1300 275 820 CUSTOMER SERVICE: 1300 770 723 EMAIL: INFO@PARAMOUNTSAFETY.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, HIGHBROOK. EAST TAMAKI, AUCKLAND 2013 TECH SUPPORT: 0800 888 778 CUSTOMER SERVICE: 0800 888 778 EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ





TECHNOLOGY











AVAILABLE IN

PRODUCT CODE	UOM	MOQ	CTN QTY
6600	EACH	12	144
6602	EACH	12	144

CARE INSTRUCTIONS

Avoid exposure to liquids/solvents that may cause the lens to distort/ craze as this may affect protection required.

Inspect prior to use for any pitted, crazed, damaged or heavily scratched lenses and replace if signs of deterioration appear.

For heavily soiled applications, wash under running water to remove excess grit and wipe clean with Pro Choice Safety Gear Lens Cleaning Wipes.

For product longevity store in a clean microfiber Pro Choice Safety Gear Spectacle Pouch.

STANDARDS

CERTIFIED TO:

AS/NZS 1337.1:2010 SAI Global LICENSE NUMBER-SMKH 25492



CLEAR LENS - CATEGORY 0 - 91% (Tv) LUMINOUS TRANSMITTANCE- OUTDOOR UNTINTED

SMOKE LENS - CATEGORY 3 - 15% (Tv)

LUMINOUS TRANSMITTANCE OUTDOOR TINTED



PROCHOICESAFETYGEAR.COM PARAMOUNTSAFETY.COM