HAND PROTECTION ARAX CUT F IMPACT GLOVES

PRODUCT DATA SHEET: AIG-(SIZE)







FEATURES AND BENEFITS

- Highest Level F Cut Protection.
- ANSI Level 1 Impact rated to protect back of hand and fingers.
- Nitrile Sand Dip for extreme wet and oily grip.
- Seamless construction for enhanced comfort and breathability.
- Certified Protection for the most extreme work environements.
- Velcro Cuff Closure for easy fitting.

APPLICATIONS

The Pro Choice Safety Gear range of hand protection is ideal for protection against risks associated with a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to:

Fabrication, Heavy Assembly, Construction Trades, Petroleum Industry, Automotive Manufacturing, Scaffolding and Dogging, Mining, Demolition and Recycling.

PRODUCT DETAILS

Material:	13 Gauge Seamless Arax [®] Liner	
Dip:	Foam Nitrile Dip	
Cuff Type:	Velcro Cuff Closure	
Colour:	Black	
Sizes:	7, 8, 9, 10, 11, 12	

AVAILABLE IN

QUANTITY	CARTON
12 pairs	120 pairs
	``

PROCHOICE SAFETY GEAR AUSTRALIA

2/980 ABERNETHY ROAD, HIGH WYCOMBE, WA 6057 TECH SUPPORT: 1300 275 820 CUSTOMER SERVICE: 1300 770 723 EMAIL: INFO@PROCHOICESAFETYGEAR.COM

PROCHOICE SAFETY GEAR NEW ZEALAND 7 SIR WOOLF FISHER DRIVE, HIGHBROOK, EAST TAMAKI, AUCKLAND 2013

EAST TAMAKI, AUCKLAND 2013 TECH SUPPORT: 0800 888 778 CUSTOMER SERVICE: 0800 888 778 EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

CUT TEST - ISO13997

Amount of pressure required to make an incision over a 20mm travel distance using a razor sharp blade.

PERFORMANCE LEVEL	NEWTON	WEIGHT
А	<2	200g
В	≥5	500g
С	≥10	1kg
D	≥15	1.5kg
E	≥22	2.2kg
F	≥30	3.0kg

STANDARDS

CE CATEGORY:

II Intermediary risks in accordance with:

ANSI/ISEA 138

EN450 AS/NZS 2161.2:2020 General Requirements EN388 AS/NZS 2161.3:2020 Protection Against Mechanical Risks Results: 4X42FP







PROCHOICESAFETYGEAR.COM PIPANZ.COM