

RESPIRATORY GEAR

P2 DISPOSABLE RESPIRATOR WITH VALVE & ACTIVE CARBON FILTER

PRODUCT DATA SHEET: PC531



PRODUCT CODE:
PC531



FEATURES AND BENEFITS

- Suitable for use with dust, smoke, mist & fume.
- Activated carbon layer reduces exposure to nuisance levels of organic vapor and odour.
- Lightweight moulded design with foam nose seal for comfort and superior fit.
- ProValve for increased exhalation efficiency and comfort, reduces heat build-up under mask.
- Easily worn with glasses & goggles.
- P2 Certified to AS/NZS 1716:2012 Respiratory Protective Devices.
- Dual latex free elastic straps for ease of donning & doffing.
- Resealable bag for hygienic storage.

AVAILABLE IN

PRODUCT CODE	UOM	MOQ	CTN QTY
PC531	BOX	1	20

PRODUCT DETAILS

Straps: Latex-Free Rubber
Filter Media: Polypropylene Melt-blown
Weight: 15g +/- 5g each
Nose Flange: PU Foam

CARE INSTRUCTIONS

Shelf life of the unopened product is three (3) years from date of manufacture when stored within the temperature range of -5°C to +50°C and less than 80% relative humidity.

End of shelf life date is marked on the product packaging. Before initial use, always check that the product is within the stated shelf life. When storing or transporting this product use original packaging provided.

Ensure disposable mask is correctly fitted prior to each use and conduct annual fit testing in accordance with AS/NZS 1715:2009.



HYGIENIC



PARTICULATE PROTECTION



RETAINS SHAPE



VALUE

WARNINGS AND USE LIMITATIONS

- Facial hair has the potential to compromise the required protective seal of the respirator.
- Ensure adequate oxygen levels are present.
- Ensure the contamination is known and the respirator is suitable for the application.
- Replace when taste, smell or the breathing resistance is high.
- Store in a clean, resealable storage device.

STANDARDS

CERTIFIED TO:
AS/NZS 1716:2012 Respiratory Protective Devices

Certified by Benchmark
Identification number: BMP547903

To be used in conjunction with:
AS/NZS 1715:2009 Selection, Use and Maintenance of Respiratory Protective Equipment



AS/NZS 1716:2012
ID No: BMP547903

CLASSIFICATION	EFFICIENCY	EXAMPLE OF CONTAMINANTS/USES
P1	80% (Particles to 1µm micron = 0.001mm size)	Dust
P2	94% (particles to 0.3µm micron = 0.0003mm size)	Toxic dusts including asbestos, welding fumes
P3	99.95% (particles to <0.3µm micron = less than 0.0003mm size)	Toxic dusts including asbestos, welding fumes, full face and powered air performance at P3 only

PARAMOUNT SAFETY PRODUCTS AUSTRALIA
12 FELLOWSHIP ROAD,
GNANGARA, WA 6077
TECH SUPPORT: 1300 275 820
CUSTOMER SERVICE: 1300 770 723
EMAIL: INFO@PROCHOICESAFETYGEAR.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND
7 SIR WOOLF FISHER DRIVE, Highbrook,
EAST TAMAKI, AUCKLAND 2013
TECH SUPPORT: 0800 888 778
CUSTOMER SERVICE: 0800 888 778
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM
PARAMOUNTSAFETY.COM

PRO
PRO CHOICE SAFETY GEAR
FROM
PARAMOUNT
SAFETY PRODUCTS