

RESPIRATORY GEAR

PROMESH® RESPIRATOR P2

PRODUCT DATA SHEET: PC821



PRODUCT CODE:
PC821



FEATURES AND BENEFITS

- Suitable for use with dust, smoke, mist & fume
- Lightweight moulded design with mesh shell to resist collapsing in heat and humidity
- Complete mask seal lining for increased comfort and fit
- Easily worn with glasses & goggles.
- P2 Certified to AS/NZS 1716:2012 Respiratory Protective Devices
- Dual QuickLock adjustable straps for ease of donning & doffing.
- Resealable bag for hygienic storage

AVAILABLE IN

PRODUCT CODE	UOM	MOQ	CTN QTY
PC821	BOX	1	20

PRODUCT DETAILS

Straps: Textile Elastic / LLDPE
Mask Lining: Terylene + PU
Outer Mesh: EVA + LDPE
Filter Media: Polypropylene Melt-Blown
Weight: 24.6g ± 2

CARE INSTRUCTIONS

Shelf life of the unopened product is three (3) years from date of manufacture when stored within the temperature range of -5°C to +50°C and less than 80% relative humidity.

End of shelf life date is marked on the product packaging. Before initial use, always check that the product is within the stated shelf life. When storing or transporting this product use original packaging provided.

Ensure disposable mask is correctly fitted prior to each use and conduct annual fit testing in accordance with AS/NZS 1715:2009.



COMFORT



PARTICULATE PROTECTION



RETAINS SHAPE



REUSABLE

WARNINGS AND USE LIMITATIONS

- Facial hair has the potential to compromise the required protective seal of the respirator
- Ensure adequate oxygen levels are present
- Ensure the contamination is known and the respirator is suitable for the application
- Replace when taste, smell or the breathing resistance is high
- Store in a clean, resealable storage device

STANDARDS

CERTIFIED TO:
AS/NZS 1716:2012 Respiratory Protective Devices
 Certified by Benchmark
Identification number: BMP547903



AS/NZS1716:2012
 ID No: **BMP547903**

To be used in conjunction with:
AS/NZS 1715:2009 - Selection, Use and Maintenance of Respiratory Protective Equipment

CLASSIFICATION	EFFICIENCY	EXAMPLE OF CONTAMINANTS/USES
P1	80% (Particles to 1µm micron = 0.001mm size)	Dust
P2	94% (particles to 0.3µm micron = 0.0003mm size)	Toxic dusts including asbestos, welding fumes
P3	99.95% (particles to <0.3µm micron = less than 0.0003mm size)	Toxic dusts including asbestos, welding fumes, full face and powered air performance at P3 only

PARAMOUNT SAFETY PRODUCTS AUSTRALIA
 12 FELLOWSHIP ROAD,
 GNANGARA, WA 6077
 TECH SUPPORT: 1300 275 820
 CUSTOMER SERVICE: 1300 770 723
 EMAIL: INFO@PROCHOICESAFETYGEAR.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND
 7 SIR WOOLF FISHER DRIVE, HIGHBROOK,
 EAST TAMAKI, AUCKLAND 2013
 TECH SUPPORT: 0800 888 778
 CUSTOMER SERVICE: 0800 888 778
 EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM
PARAMOUNTSAFETY.COM

PRO
 PRO CHOICE SAFETY GEAR
 FROM
PARAMOUNT
 SAFETY PRODUCTS