

# RESPIRATORY GEAR

## P2 FILTERS TO SUIT PRO MAXI MASK 2000™ & JSP FORCE TYPHOON MASK RESPIRATORS

PRODUCT DATA SHEET: PCP2



PRODUCT CODE:  
PCP2



### FEATURES AND BENEFITS

- Certified to AS/NZS 1716:2012 Respiratory Protective Devices.
- For use on the JSP Force Typhoon Masks and PRO Maxi Mask 2000 options.
- Twin filter design provides a more balanced fit, lower breathing resistance and improves field of vision.
- P2 filters protects against mechanical and thermally generated particles.
- Easy 'lock-on' system.
- Kit complete with 2 x P2 pads and retainer caps.

### AVAILABLE IN

PRODUCT CODE	MOQ	CTN QTY
PCP2	1 pair	50 pairs

### PRODUCT DETAILS

Weight: 110g per filter

### CARE INSTRUCTIONS

Shelf life of the unopened product is 3 years from date of manufacture when stored within temperature range of -20°C to +25°C and less than 80% relative humidity.

Manufactured date printed onto filters, maximum life span is 6 months once filter is removed from original packaging, however life span is determined by the wearers ability to taste, smell or notice increase in breathing resistance.

Ensure mask is correctly fitted prior to each use and conduct annual fit testing in accordance with AS/NZS 1715:2009.

### APPLICATIONS

The Pro Choice Safety Gear range of respiratory gear is ideal for protection against risks associated with a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to: Agriculture, aviation, automotive, chemical manufacturing, construction, forestry, heavy engineering, manufacturing, metal processing, mining and quarrying, transportation.



### WARNINGS AND USE LIMITATIONS

1. Facial hair has the potential to compromise the required protective seal of the respirator.
2. Ensure adequate oxygen levels are present.
3. Ensure the contamination is known and the respirator is suitable for the application.
4. Replace when taste, smell or the breathing resistance is high.
5. Store in a clean resealable storage device.

### STANDARDS

**CERTIFIED TO:**  
AS/NZS 1716:2012 Respiratory Protective Devices.  
Certified by SAI Global

To be used in conjunction with:  
AS/NZS 1715:2009 Selection, use and maintenance  
of respiratory protective equipment.



AS/NZS 1716:2012  
Lic 1508

CLASSIFICATION	EFFICIENCY	EXAMPLE OF CONTAMINANTS/USES
P1	80% (Particles to 1µm micron = 0.001mm size)	Dust
P2	94% (particles to 0.3µm micron = 0.0003mm size)	Toxic dusts including asbestos, welding fumes
P3	99.95% (particles to <0.3µm micron = less than 0.0003mm size)	Toxic dusts including asbestos, welding fumes, full face and powered air performance at P3 only