

HEARING PROTECTION VIPER® HARD HAT EARMUFFS

PRODUCT DATA SHEET: HHEM



PRODUCT CODE:
HHEM



FEATURES AND BENEFITS

- Certified to AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5, SLC_{80} 26dB.
- Hearing protection for noise levels to 111dB(A).
- Hi-vis orange for visual identification.
- 25mm Cap attachment slot to suit all Pro Choice Safety Gear cap style hard hats.
- Compatible with Pro Choice Safety Gear hard hat brow guards (HHBGE/HHBGE-B).
- Solid, lightweight ear cup construction.
- High quality ear cushions.
- Inner foam & headband cushion provides comfort during extended wear.
- Low clamping force applies minimum pressure while maintaining a tight, snug seal.
- Hygiene kits assist in extending the performance & lifetime of the earmuffs.

AVAILABLE IN

PRODUCT CODE	COLOUR	UOM	MOQ	CTN QTY
HHEM	HVO	EACH	1	25

CARE INSTRUCTIONS

It is recommended that cushions be wiped clean at the end of use each day. Inspect regularly for damage, deterioration or hardening. Replace prior to further use. Proper maintenance is key for sustained performance of noise reduction equipment.

Clean cushions & liners regularly using warm soapy water. Dry prior to use. Replace hygiene kit/cushions should they begin to show signs of deterioration or hardening.



PRODUCT DETAILS

Weight:	200g
Clamping Force:	9.4N
Colour:	Hi-Vis Orange
Size:	Standard One Size

TEST DATA

ATTENUATION TABLE (IN DECIBELS)							
Frequency Hz	125	250	500	1000	2000	4000	8000
Mean Attenuation	11.8	18.1	24.7	31.2	31.1	37.7	40.5
Standard Deviation	2.2	4.3	3.8	6.6	3.6	4.5	2.4
Mean-Minus-Standard Deviation Attenuations	9.6	13.8	20.9	24.6	27.5	32.7	38.1

SLC_{80} Value is 26 (Class 5)

APPLICATIONS

The Pro Choice Safety Gear range of hearing protection is ideal for protection against noise generated from a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to: Agriculture, aviation, automotive, chemical manufacturing, construction, forestry, heavy engineering, metal processing, mining and quarrying, welding, woodworking.

STANDARDS

CERTIFIED TO:
AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5, SLC_{80} 26dB.

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 111dB(A) assuming an 85dB(A) criterion. A lower criterion may require a higher protector class.



AS/NZS 1270:2002
SMKH20580

PARAMOUNT SAFETY PRODUCTS AUSTRALIA
12 FELLOWSHIP ROAD,
GNANGARA, WA 6077
TECH SUPPORT: 1300 275 820
CUSTOMER SERVICE: 1300 770 723
EMAIL: INFO@PARAMOUNTSAFETY.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND
7 SIR WOOLF FISHER DRIVE, Highbrook,
EAST TAMAKI, AUCKLAND 2013
TECH SUPPORT: 0800 888 778
CUSTOMER SERVICE: 0800 888 778
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM
PARAMOUNTSAFETY.COM

PRO
PRO CHOICE SAFETY GEAR
FROM
PARAMOUNT
SAFETY PRODUCTS